

WISeNET

hanwhasecurity.com

Never miss a thing



# WISeNET P series

Premium Multi-sensor cameras

Hanwha Techwin America  
500 Frank W. Burr Blvd. Suite 43 Teaneck, NJ 07666  
Toll Free: +1.877.213.1222  
www.hanwhasecurity.com

© 2018 Hanwha Techwin Co., Ltd. All rights reserved.

DESIGN AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE  
Under no circumstances, this document shall be reproduced, distributed or changed,  
partially or wholly, without formal authorization of Hanwha Techwin Co., Ltd.  
M.H-1808



First edition 02-2018



## Cover wide areas with one camera

Wisenet P series multi-sensor cameras are equipped with multiple sensors, which means that it can effectively monitor wide areas with just one camera.

- Multi-directional cameras can simultaneously monitor multiple directions without any blind spots. When it is combined with a PTZ camera, it provides a detailed view of the desired image through its effective zoom-in function.
- Panoramic cameras provide a wide panoramic view within a single camera by stitching 4 images from each sensors.

By installing Wisenet multi-sensor cameras, the cost of system installation and maintenance is reduced significantly while successfully monitoring wide areas.

### Multi-directional Camera



**PNM-7000VD**  
4MP (2MP x 2ea)  
with selectable  
lens module



**PNM-9000VQ**  
Max. 20MP (5MP/2MP x  
4ea) with selectable lens  
module



**PNM-9080VQ**  
8MP (2MP x 4ea)



**PNM-9081VQ**  
20MP (5MP x 4ea)

### Multi-directional Camera with PTZ



*Coming soon*  
**PNM-9320VQP**  
Max. 22MP  
(2MP 32x PTZ + 5MP/2MP x  
4ea) with selectable lens

### Panoramic Camera



**PNM-9020V**  
7.3MP (2MP x 4ea)



*Coming soon*  
**PNM-9030V**  
15MP (5MP x 4ea)

## Multiple view modes

Choose from a variety of viewing options that fit your needs by using the broad line-up of Wisenet multi-sensor cameras.

### Full HD Multi-directional Camera

PNM-7000VD 4MP (2MP x 2ea) with selectable lens module

PNM-7000VD is able to simultaneously monitor two areas through multiple angles by installing two lens modules in one surveillance camera, which removes the needs for multiple cameras and reduces the Total Cost of Ownership (TCO).



2CH Multi-directional Camera

PNM-7000VD



### Full HD compatible fixed lens

According to the desired direction and viewing angle, you are able to select 2M 2.4, 2.8, 3.6 and 6mm lenses. The full HD video feature enables clear and sharp monitoring. By installing two 2.4mm lenses, monitoring up to 270 degree can be achieved, making it perfect for surveillance of large spaces such as parks, parking lots and shopping malls.



SLA-2M2400D 2.4mm Fixed Lens



SLA-2M3600D 3.6mm Fixed Lens




SLA-2M6000D 6.0mm Fixed Lens

### Premium Multi-directional Camera

PNM-9081VQ 20MP (5MP x 4ea)  
 PNM-9080VQ 8MP (2MP x 4ea)  
 PNM-9000VQ Max. 20MP (5MP/2MP x 4ea)  
 with selectable lens module

Multi-directional cameras have four sensors in one camera. The four sensors in the multi-directional camera move independently on top of the tracks enabling users to monitor a complete 360° view simultaneously without any blind spots. In addition, one of the sensors can easily be removed and attached in the center of the camera, allowing for flexible set-up.



### Natural and clearer image

When using a fisheye camera, it brings low image quality and image distortion at each edge of the image. However, the Multidirectional camera with 4 sensors brings almost non image distortion and shows clearer image at each edge of the image.



Fisheye Camera



Low image quality and image distortion at the edges.



Multi-directional Camera


Clearer image and almost non distortion at the edges.

### Multi-directional Camera with PTZ

PNM-9320VQP Max. 22MP (2MP 32x PTZ + 5MP/2MP x 4ea) with selectable lens module *Coming soon*

PNM-9320VQP is a 5CH camera that combines four sensor multi-directional camera and 2MP 32x PTZ camera. The multi-directional camera can monitor a 360° wide area while the PTZ camera zooms in to the desired area for closer inspection.

PNM-9320VQP has a built-in 100/1000 SFP slots in its installation base which sends high resolution images to distanced locations through a network without any data damage.



When an event is detected, the PTZ can either zoom into the event or the preset location by using the advanced handover to PTZ function.

Smart Zoom mode

### Advanced handover to PTZ

PNM-9320VQP showcases the best of 2MP 32x PTZ camera through an advanced handover function composed of preset mode and smart zoom mode. When the multi-directional camera detects an event, it automatically links to PTZ camera which carries out zoom-in and track functions.

When using preset mode, PTZ camera zooms in to the position that the users preset, while smart zoom mode automatically zooms into the area where event is detected. Create your own monitoring scenario that fit your needs by using the two modes of advanced handover to PTZ function.

## Panoramic Camera

PNM-9020V 7.3MP (2MP x 4ea)  
 PNM-9030V 15MP (5MP x 4ea) *Coming soon*

Panoramic cameras provide a wide panoramic view within a single camera instead of installing 4 cameras. It offers a seamless single image by merging 4 images from each sensors.



### Single Panorama image (PNM-9020V)

PNM-9020V is a single channel camera that provides 7.3MP of panoramic image with 180° horizontal and 84° vertical field of view. The camera provides a single piece of high resolution panoramic view by stitching 4 images to monitor a wide range of area.



### Single Panorama + Original + Crop images (PNM-9030V)

PNM-9030V can stream a single panoramic 15MP image merged from the 4 original images, 4 of the original 5MP images from each sensor, and 2 of the 2MP crop images.



## Selectable and changeable multiple lens (PNM-7000VD/9000VQ/9320VQP only)


With the new modular design Multi-sensors it provide the flexibility not just to pick the correct lens focused in the factory but also the desired resolution for every head (PNM-9000VQ and PNM-9320VQP). So out of one camera some heads can be 2MP and other can be 5MP depends on the application.  
 \* PNM-7000VD will allow the lens modular design but it can only accept 2MP lens modules only

	1/2.8" 2MP Lens				1/1.8" 5MP Lens			1/2.8" 2MP Lens
	2.4mm fixed	2.8mm fixed	3.6mm fixed	6.0mm fixed	3.7mm fixed	4.6mm fixed	7.0mm fixed	12mm fixed
PNM-7000VD	✓	✓	✓	✓				
PNM-9000VQ	✓	✓	✓	✓	✓	✓	✓	
PNM-9320VQP	✓	✓	✓	✓	✓	✓	✓	✓

※The applicable lens differs for each camera.

## Optimized for indoor and outdoor environments


Wisenet P series panoramic and multi-directional cameras are suitable to monitor even the smallest details in a wide area. They are ideal for applications such as warehouse, shopping mall entrances, train stations, parking lots, and more.



- Warehouse
- Mall entrance
- City Surveillance
- Airport
- Parking lot
- Stadium
- Square
- Distribution center
- Crossroads
- Train station

## Improve bandwidth by up to 99% using WiseStream II

When Hanwha Techwin's original video compression technology WiseStream II is combined with H.265 compression, the bitrate data is reduced by up to 99% compared to current H.264 technology. The costs of configuring and maintaining the system are also greatly reduced, while still maintaining the same pixels and high quality.



WiseStream II OFF : 7160kbps  
WiseStream II ON : 74kbps

WiseStream II OFF : 7260kbps  
WiseStream II ON : 1817kbps

※Not available on PNM-9020

## True WDR performance

Even with backlight, Wisenet's cutting-edge WDR technology addresses a limitation found in conventional WDR cameras while producing clear and vivid images. WDR improves the accuracy of an image by resolving the difference in brightness.



Conventional

Wisenet WDR 150dB actual footage

※150dB is available in 2MP cameras and 120dB is available in 5MP cameras.  
※PNM-9020

## Hallway view for monitoring vertical shaped areas

In a vertical shaped environment, such as corridors, hallways, tunnels, or aisles, traditional horizontal shaped videos focus on unnecessary edges of the area causing bandwidth and storage waste. The Hallway view, 3 : 4 and 9 : 16 aspect ratio image is created : a vertically oriented video that maximizes image quality in narrow locations.



Conventional

Hallway View




## A comprehensive range of intelligent video analytics

Wisenet P series multi-sensor cameras support a variety of exclusive video and audio analytics, providing enhanced monitoring solutions and market intelligence.



※Supported video analytics may vary depending on the product.

# Accessory configuration



# Product Comparison



PNM-7000VD



SLA-2M6000D



SLA-2M3600D



SLA-2M2800D



SLA-2M2400D

Resolution	4MP (2MP x 2ea)	2MP	2MP	2MP	2MP
Imaging Device	-	1/2.8" 2MP CMOS	1/2.8" 2MP CMOS	1/2.8" 2MP CMOS	1/2.8" 2MP CMOS
Video Compression	H.265, H.264, MJPEG	-	-	-	-
Resolution / Frame Rate	2ea x 2M / 60fps	-	-	-	-
Streaming Capacity	Multiple (Up to 10 Profiles)	-	-	-	-
Max. User Access	20 (Unicast)	-	-	-	-
Min. Illumination	-	Color : 0.055Lux B/W : 0.055Lux			
Video Output	CVBS 1.0Vpp	-	-	-	-
Lens	-	6.0mm fixed (F2.0)	3.6mm fixed (F2.0)	2.8mm fixed (F2.0)	2.4mm fixed (F2.0)
Angular Field of View	-	H : 50.4° / V : 28.8° / D : 58.1°	H : 94.8° / V : 49.3° / D : 114.3°	H : 107.4° / V : 62.2° / D : 122.0°	H : 135.4° / V : 71.2° / D : 161.6°
Focus Control	-	Fixed	Fixed	Fixed	Fixed
IR Viewable Length	-	-	-	-	-
Pan / Tilt / Rotate	-	-	-	-	-
Day & Night	Electrical	Electrical	Electrical	Electrical	Electrical
Backlight Compensation	WDR (150dB)	WDR (150dB)	WDR (150dB)	WDR (150dB)	WDR (150dB)
Digital Noise Reduction	SSNRV (2D+3D Noise filter)	-	-	-	-
Digital Image Stabilization	Support	-	-	-	-
Video & Audio Analytics	Tampering, Loitering, Directional detection, Fog detection, Virtual line, Enter/Exit, (Dis)Appear, Motion detection, Face detection	-	-	-	-
Protocol	ONVIF profile S, SUNAPI	-	-	-	-
Alarm I/O	-	-	-	-	-
Audio	-	-	-	-	-
Edge Storage	SD/SDHC/SDXC, Local PC	-	-	-	-
Environment Protection	IP66, IK10	-	-	-	-
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F)	-	-	-	-
Power	Max.12.95W (PoE)	-	-	-	-
Dimensions (WxHxD) / Weight	Ø161.0 x 73.0mm (Ø6.34" x 2.87") 840g (1.85 lb)	Ø35.5 x 27.9mm (1.4" x 1.1") 27g (0.06 lb)	Ø35.5 x 27.9mm (1.4" x 1.1") 27g (0.06 lb)	Ø35.5 x 27.9mm (1.4" x 1.1") 27g (0.06 lb)	Ø35.5 x 27.9mm (1.4" x 1.1") 27g (0.06 lb)
Additional Features	Multi-directional camera, Defog, WiseStream II, Hallway View	Lens module for PNM-7000VD			



PNM-9081VQ



PNM-9080VQ



PNM-9030V



PNM-9020V

Resolution	20MP (5MP x 4ea)	8MP (2MP x 4ea)	15MP (5MP x 4ea)	7.3MP (2MP x 4ea)
Imaging Device	1/1.8" 6MP CMOS x 4	1/2.8" 2.38MP CMOS x 4	15MP (5MP x 4ea)	7.3MP (2MP x 4)
Video Compression	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG
Resolution / Frame Rate	5MP / 30fps	2MP / 60fps	15MP / 30fps (H.265, H.264)	7.3MP / 30fps (H.265, H.264)
Streaming Capacity	Multiple (Up to 40 Profiles)	Multiple (Up to 40 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 3 Profiles)
Max. User Access	20 (Unicast)	20 (Unicast)	20 (Unicast)	15 (Unicast)
Min. Illumination	Color : 0.07Lux B/W : 0.007Lux	Color : 0.015Lux B/W : 0.0015Lux	Color : 0.15Lux B/W : 0.01Lux	Color : 0.3Lux B/W : 0.03Lux
Video Output	CVBS 1.0Vpp (selectable CVBS per channel)	CVBS 1.0Vpp (selectable CVBS per channel)	Micro USB type B	-
Lens	3.6 ~ 9.4mm (2.6x) motorized V/F (F1.2)	2.8 ~ 12mm (4.3x) motorized V/F F1.4(Wide) / F3.6(Tele)	4.0mm fixed (F2.0)	3.6mm fixed (F2.0)
Angular Field of View	H : 102.5°(Wide) ~ 38.7°(Tele) / V : 74.2°(Wide) ~ 29.0°(Tele) / D : 135.5°(Wide) ~ 48.6°(Tele)	H : 119.5°(Wide) ~ 27.9°(Tele) / V : 62.8°(Wide) ~ 15.7°(Tele) / D : 142.1°(Wide) ~ 32.0°(Tele)	[Total 4 Sensor] 180° mode - H : 180° / V : 73° 220° mode - H : 220° / V : 54°	[Total 4 Sensor] H : 180° / V : 84°
Focus Control	Simple focus (motorized V/F) / Manual	Simple focus (motorized V/F) / Manual	Fixed	-
IR Viewable Length	-	-	-	-
Pan / Tilt / Rotate	Quad mode : ±30° / 10° ~ 41° / ±90°, Center mode : ±60° / 10° ~ 41°, 10° ~ 90° (CH2/Center) / ±90°	Quad mode : ±30° / 10° ~ 41° / ±90°, Center mode : ±60° / 10° ~ 41°, 10° ~ 90° (CH2/Center) / ±90°	0° ~ 355° / 0° ~ 60° / -	0° ~ 355° / 0° ~ 60° / -
Day & Night	True (ICR)	True (ICR)	True (ICR)	True (ICR)
Backlight Compensation	WDR (120dB)	WDR (150dB)	WDR (120dB)	WDR (120dB)
Digital Noise Reduction	SSNRV (2D+3D Noise filter)	SSNRV (2D+3D Noise filter)	SSNRV (2D+3D Noise filter)	SSNRV (2D+3D Noise filter)
Digital Image Stabilization	Support (Built in Gyro sensor)	Support (Built in Gyro sensor)	-	-
Video & Audio Analytics	Tampering, Loitering, Directional detection, Defocus detection, Fog detection, Virtual line, Enter/Exit, (Dis)Appear, Motion detection	Tampering, Loitering, Directional detection, Defocus detection, Fog detection, Virtual line, Enter/Exit, (Dis)Appear, Motion detection	Tampering, Loitering, Directional detection, Virtual line, Enter/Exit, (Dis)Appear, Audio detection, Motion detection, Heatmap, Sound classification	Tampering, Virtual line, Enter/Exit, (Dis)Appear, Audio detection, Defocus detection, Digital Auto tracking, Heatmap
Protocol	ONVIF profile S, SUNAPI	ONVIF profile S, SUNAPI	ONVIF Profile S/G, SUNAPI	ONVIF profile S/G, SUNAPI
Alarm I/O	1 / 1	1 / 1	1 / 1	1 / 1
Audio	-	-	Bi-Directional	Bi-Directional
Edge Storage	SD/SDHC/SDXC, Local PC	SD/SDHC/SDXC, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC
Environment Protection	IP66, IK10	IP66, IK10	IP66, IK10	IP66, IK10
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F)	-40°C ~ +55°C (-40°F ~ +131°F)	-40°C ~ +55°C (-40°F ~ +131°F)	-40°C ~ +55°C (-40°F ~ +131°F) * Start up above -35°C (-31°F)
Power	Max. 28.8W (12V DC) Max. 33.6W (HPoE)	Max. 21.6W (12V DC) Max. 25.5W (PoE+)	Max 21.0W (12V DC) Max 25.5W (PoE+)	Max. 21.0W - Heater on (12V DC) Max. 25.5W - Heater on (PoE+)
Dimensions (WxHxD) / Weight	Ø314 x 152mm (Ø12.36" x 5.98") 4.89kg (10.78 lb)	Ø314 x 152mm (Ø12.36" x 5.98") 4.83kg (10.65 lb)	TBD	Ø199.0 x 143.5mm (Ø7.83" x 5.65") 2.03kg (4.48 lb)
Additional Features	Multi-directional camera, Hallway View, P-Iris, Defog, WiseStream II	Multi-directional camera, Hallway View, P-Iris, Defog, WiseStream II	Handover, Multi-sensor camera, WiseStream II	Handover, Multi-sensor camera, Defog, WiseStream



	PNM-9000VQ	SLA-5M7000Q	SLA-5M4600Q	SLA-5M3700Q
Resolution	Max. 20MP (2MP/5MP x 4ea)	5MP	5MP	5MP
Imaging Device	-	1/1.8" 5MP CMOS	1/1.8" 5MP CMOS	1/1.8" 5MP CMOS
Video Compression	H.265, H.264, MJPEG	-	-	-
Resolution / Frame Rate	5MP / 30fps, 2M / 60fps	-	-	-
Streaming Capacity	Multiple (Up to 10 Profiles)	-	-	-
Max. User Access	20 (Unicast)	-	-	-
Min. Illumination	-	Color : 0.16Lux, B/W : 0.16Lux	Color : 0.16Lux, B/W : 0.16Lux	Color : 0.16Lux, B/W : 0.16Lux
Video Output	CVBS 1.0Vpp	-	-	-
Lens	-	7.0mm fixed (F1.6)	4.6mm fixed (F1.6)	3.7mm fixed (F1.6)
Angular Field of View	-	H : 50.7° / V : 37.8° / D : 63.8°	H : 77.9° / V : 57.9° / D : 98.7°	H : 97.5° / V : 71.9° / D : 126.2°
Focus Control	-	Fixed	Fixed	Fixed
IR Viewable Length	-	-	-	-
Pan / Tilt / Rotate	-	-	-	-
Day & Night	Electrical	Electrical	Electrical	Electrical
Backlight Compensation	WDR 150dB(2MP), 120dB(5MP)	WDR (120dB)	WDR (120dB)	WDR (120dB)
Digital Noise Reduction	SSNRV (2D+3D Noise filter)	-	-	-
Digital Image Stabilization	Support	-	-	-
Video & Audio Analytics	Tampering, Loitering, Directional detection, Fog detection, Virtual line, Enter/Exit, (Dis)Appear, Motion detection, Face detection, Defocus detection	-	-	-
Protocol	ONVIF Profile S, SUNAPI	-	-	-
Alarm I/O	-	-	-	-
Audio	-	-	-	-
Edge Storage	SD/SDHC/SDXC, Local PC	-	-	-
Environment Protection	IP66, IK10	-	-	-
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F)	-	-	-
Power	25.5W (PoE+)	-	-	-
Dimensions (WxHxD) / Weight	Ø253x130mm (Ø9.96" x 5.11") 3.0 kg (6.7 lb)	Ø 35.5 x 35.9 mm (Ø 1.39" x 1.41") 35g (0.08 lb)	Ø 35.5 x 35.9 mm (Ø 1.39" x 1.41") 35g (0.08 lb)	Ø 35.5 x 35.9 mm (Ø 1.39" x 1.41") 35g (0.08 lb)
Additional Features	Multi-directional camera, Defog, WiseStream II HallwayView	Lens module for PNM-9000VQ	Lens module for PNM-9000VQ	Lens module for PNM-9000VQ

	SLA-2M6000Q	SLA-2M3600Q	SLA-2M2800Q	SLA-2M2400Q
Resolution	2MP	2MP	2MP	2MP
Imaging Device	1/2.8" 2MP CMOS	1/2.8" 2MP CMOS	1/2.8" 2MP CMOS	1/2.8" 2MP CMOS
Video Compression	-	-	-	-
Resolution / Frame Rate	-	-	-	-
Streaming Capacity	-	-	-	-
Max. User Access	-	-	-	-
Min. Illumination	Color : 0.055Lux, B/W : 0.055Lux			
Video Output	-	-	-	-
Lens	6.0mm fixed (F2.0)	3.6mm fixed (F2.0)	2.8mm fixed (F2.0)	2.4mm fixed (F2.0)
Angular Field of View	H : 50.4° / V : 28.8° / D : 58.1°	H : 94.8° / V : 49.3° / D : 114.3°	H : 107.4° / V : 62.2° / D : 122.0°	H : 135.4° / V : 71.2° / D : 161.6°
Focus Control	Fixed	Fixed	Fixed	Fixed
IR Viewable Length	-	-	-	-
Pan / Tilt / Rotate	-	-	-	-
Day & Night	Electrical	Electrical	Electrical	Electrical
Backlight Compensation	WDR (150dB)	WDR (150dB)	WDR (150dB)	WDR (150dB)
Digital Noise Reduction	-	-	-	-
Digital Image Stabilization	-	-	-	-
Video & Audio Analytics	-	-	-	-
Protocol	-	-	-	-
Alarm I/O	-	-	-	-
Audio	-	-	-	-
Edge Storage	-	-	-	-
Environment Protection	-	-	-	-
Operating Temperature	-	-	-	-
Power	-	-	-	-
Dimensions (WxHxD) / Weight	Ø 35.5 x 35.9 mm (Ø 1.39" x 1.41") 35g (0.08 lb)	Ø 35.5 x 35.9 mm (Ø 1.39" x 1.41") 35g (0.08 lb)	Ø 35.5 x 35.9 mm (Ø 1.39" x 1.41") 35g (0.08 lb)	Ø 35.5 x 35.9 mm (Ø 1.39" x 1.41") 35g (0.08 lb)
Additional Features	Lens module for PNM-9000VQ			



PNM-9320VQP



SLA-5M7000P



SLA-5M4600P



SLA-5M3700P

Resolution	Max. 22MP (2MP 32x PTZ + 2MP/5MP x 4ea)	5MP	5MP	5MP
Imaging Device	1/2.8" 2.4MP CMOS (PTZ)	1 / 1.8" 5MP CMOS	1 / 1.8" 5MP CMOS	1 / 1.8" 5MP CMOS
Video Compression	H.265, H.264, MJPEG	-	-	-
Resolution / Frame Rate	5MP / 30fps, 2M / 60fps	-	-	-
Streaming Capacity	Multiple (Up to 10 Profiles)	-	-	-
Max. User Access	20 (Unicast)	-	-	-
Min. Illumination	Color : 0.05Lux, B/W : 0.005Lux (PTZ)	Color : 0.16Lux, B/W : 0.16Lux	Color : 0.16Lux, B/W : 0.16Lux	Color : 0.16Lux, B/W : 0.16Lux
Video Output	CVBS 1.0Vpp (Multi)	-	-	-
Lens	4.44 ~ 142.6mm (Optical 32x) F1.6 (Wide) / F4.4 (Tele) (PTZ)	7.0mm fixed (F1.6)	4.6mm fixed (F1.6)	3.7mm fixed (F1.6)
Angular Field of View	H : 61.8°(Wide)~2.19°(Tele) / V : 36.2°(Wide)~1.24°(Tele) (PTZ)	H : 50.7° / V : 37.8° / D : 63.8°	H : 77.9° / V : 57.9° / D : 98.7°	H : 97.5° / V : 71.9° / D : 126.2°
Focus Control	Auto / Manual / One shot AF (PTZ)	Fixed	Fixed	Fixed
IR Viewable Length	-	-	-	-
Pan / Tilt / Rotate	360° Endless / 210° (-15°~195°) (PTZ)	-	-	-
Day & Night	Electrical (Multi), True ICR (PTZ)	Electrical	Electrical	Electrical
Backlight Compensation	WDR 150dB (2MP), 120dB (5MP)	WDR (120dB)	WDR (120dB)	WDR (120dB)
Digital Noise Reduction	SSNRV (2D+3D Noise filter)	-	-	-
Digital Image Stabilization	Support (Built in gyro sensor - PTZ)	-	-	-
Video & Audio Analytics	Tampering, Loitering, Directional detection, Fog detection, Virtual line, Enter/Exit, (Dis)Appear, Motion detection, Face detection,  Defocus detection (PTZ)	-	-	-
Protocol	ONVIF Profile S, SUNAPI	-	-	-
Alarm I/O	1 / 2	-	-	-
Audio	-	-	-	-
Edge Storage	SD/SDHC/SDXC, Local PC	-	-	-
Environment Protection	IP66, IK10	-	-	-
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F)	-	-	-
Power	Max. 65W (HPoE)	-	-	-
Dimensions (WxHxD) / Weight	Ø 367.8 x 381.5mm (Ø 144.49" x 150.20") 7.05 kg (16.1 lb)	Ø 35.5 x 35.9 mm (Ø 1.39" x 1.41") 35g (0.08 lb)	Ø 35.5 x 35.9 mm (Ø 1.39" x 1.41") 35g (0.08 lb)	Ø 35.5 x 35.9 mm (Ø 1.39" x 1.41") 35g (0.08 lb)
Additional Features	Multi-directional camera with PTZ, Defog, WiseStream II Hallway View, Auto tracking	Lens module for PNM-9320VQP	Lens module for PNM-9320VQP	Lens module for PNM-9320VQP



SLA-2M1200P



SLA-2M6000P



SLA-2M3600P



SLA-2M2800P



SLA-2M2400P

2MP	2MP	2MP	2MP	2MP
1 / 2.8" 2MP CMOS				
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
Color : 0.055Lux, B/W : 0.055Lux				
-	-	-	-	-
12mm fixed (F2.0)	6.0mm fixed (F2.0)	3.6mm fixed (F2.0)	2.8mm fixed (F2.0)	2.4mm fixed (F2.0)
H : 26.3° / V : 14.9° / D : 30.0°	H : 50.4° / V : 28.8° / D : 58.1°	H : 94.8° / V : 49.3° / D : 114.3°	H : 107.4° / V : 62.2° / D : 122.0°	H : 135.4° / V : 71.2° / D : 161.6°
Fixed	Fixed	Fixed	Fixed	Fixed
-	-	-	-	-
-	-	-	-	-
Electrical	Electrical	Electrical	Electrical	Electrical
WDR (150dB)				
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
Ø 35.5 x 35.9 mm (Ø 1.39" x 1.41") 30g (0.07 lb)	Ø 35.5 x 35.9 mm (Ø 1.39" x 1.41") 30g (0.07 lb)	Ø 35.5 x 35.9 mm (Ø 1.39" x 1.41") 30g (0.07 lb)	Ø 35.5 x 35.9 mm (Ø 1.39" x 1.41") 30g (0.07 lb)	Ø 35.5 x 35.9 mm (Ø 1.39" x 1.41") 30g (0.07 lb)
Lens module for PNM-9320VQP				

MEMO

MEMO