



PRODUCTS LISTING

May 2022

UPS, INVERTERS,
REGULATORS & SURGE PROTECTORS



Infosec Communication is certified ISO 9001 & 14001, a guarantee of its commitment to customer satisfaction and the environment.

ISO 9001, v2015 and ISO 14001, v2015 certified quality and environmental management system

UNINTERRUPTIBLE POWER SUPPLY

— APPLICATIONS : DIGITAL ENTERTAINMENT & AUTOCOMS

Series	Model	SKU	Power	Features	Communication	Equipment War.	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	Extended warranty						
											to 3 years	to 5 years					
Z1 ZenCube EX : Tower UPS - High Frequency Technology																	
	Z1 ZenCube EX 400	66072	400 VA	3 FR/SCHUKO backup outlets 2 visual indicators	-	120 000 €	2 years	166 x 161 x 86,7	2,3	9	62511	62527					
	Z1 ZenCube EX 600	66073	600 VA										120 000 €	2 years			
Z2 EX : Tower UPS - High Frequency Technology																	
	Z2 EX 550	66085	550 VA	6 FR/SCHUKO outlets (3 backup + 3 surge-protected) 1 visual indicator	USB Port Software (free download)	120 000 €	2 years	309 x 110 x 90	2,7	4	62511	62527					
	Z2 EX 700	66086	700 VA										120 000 €	2 years			
	Z2 EX 1000	66087	1000 VA										120 000 €	2 years			
Z3 ZenBox EX : Tower UPS - High Frequency Technology																	
	Z3 ZenBox EX 500	66074	500 VA	3 FR/SCHUKO backup outlets + 3 FR/SCHUKO surge-protected outlets RJ45 (In/Out) 2 visual indicators	USB Software (free download)	Unlimited	3 years	230 x 200 x 92,5	2,5	6	-	62527					
	Z3 ZenBox EX 700	66075	700 VA										4 FR/SCHUKO backup outlets + 4 FR/SCHUKO surge-protected outlets RJ45 (In/Out)	Unlimited	3 years	3,1	6
	Z3 ZenBox EX 1000	66076	1000 VA										2 visual indicators	Unlimited	3 years	3,4	6



Z1
ZenCUBE EX



Z2
EX



Z3
ZenBOX EX



Warranty extensions* offer you peace of mind for up to 3 or 5 years.

Discover all the services provided by Infosec in our dedicated documentation!



SINGLE-PHASE INPUT / SINGLE-PHASE OUTPUT UPS

UNINTERRUPTIBLE POWER SUPPLY

— APPLICATIONS : DIGITAL ENTERTAINMENT & IT, SMB

Series	Model	SKU	Power	Features	Communication	Equipment War.	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	Extended warranty	
											to 3 years	to 5 years
Zen Live : Tower UPS - Line Interactive Technology with voltage regulation system											SKU	SKU
	Zen Live 500	66081	500 VA	4 FR/SCHUKO backup outlets 1 visual indicator	-	120 000 €	2 years	245 x 163 x 90	3,5	4	62511	62527
	Zen Live 650	66082	650 VA									
	Zen Live 800	66083	800 VA	4 FR/SCHUKO backup outlets 3 visual indicators	-	120 000 €	2 years	292 x 199 x 91	5,6	4		
	Zen Live 1000	66084	1000 VA									
Zen-X : Tower UPS - Line Interactive Technology with voltage regulation system											SKU	SKU
	Zen-X 600	66070	600 VA	6 FR/SCHUKO outlets (3 backup + 3 surge-protected) RJ11/45 (In/Out) LCD display USB charger	+ USB port Software Upsilon 2000	120 000 €	2 years	293 x 202 x 93	4,2	4	62511	62527
	Zen-X 800	66071	800 VA									
	Zen-X 1000	61999	1000 VA	8 FR/SCHUKO outlets (4 backup + 4 surge-protected) RJ11/45 (In/Out) LCD display 2 USB chargers	+ USB port Software Upsilon 2000	120 000 €	2 years	309 x 202 x 93	5,8	4		



Zen Live 500/650 VA

Zen Live 800/1000 VA



Zen-X 600/800 VA

Zen-X 1000 VA

— APPLICATIONS : IT, SMB

Series	Model	SKU	Power	Features	Communication	Equipment War.	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	Extended warranty			
											to 3 years	to 5 years		
X1 IEC / EX : Tower UPS - Line Interactive Technology with voltage regulation system											SKU	SKU		
	X1 500 IEC	65923	500 VA	3 IEC backup outlets 1 IEC surge-protected outlet 1 visual indicator	-	-	2 years	300 x 101 x 142	3,7	4	62511	62527		
	X1 700 IEC	65924	700 VA											
	X1 1000 IEC	65926	1000 VA											
	X1 1250 USB IEC	65939	1250 VA	3 IEC backup outlets 1 IEC surge-protected outlet 1 visual indicator	USB Port Software : InfoPower	-	2 years	320 x 130 x 182	8,2	4			62513	62529
	X1 1600 USB IEC	65941	1600 VA											
	X1 2000 USB IEC	65943	2000 VA											
	X1 EX 500 FR/SCHUKO	65953	500 VA	2 FR/SCHUKO backup outlets 1 visual indicator	-	-	2 years	300 x 101 x 142	3,7	4	62511	62527		
	X1 EX 700 FR/SCHUKO	65954	700 VA											
	X1 EX 1000 FR/SCHUKO	65955	1000 VA											
	X1 EX 1250 USB FR/SCHUKO	65959	1250 VA	4 FR/SCHUKO backup outlets 1 visual indicator	USB Port Software : InfoPower	-	2 years	350 x 146 x 160	8,3	1			62513	62529
	X1 EX 1600 USB FR/SCHUKO	65960	1600 VA											
	X1 EX 2000 USB FR/SCHUKO	65961	2000 VA											
											62515	62531		



Ask for our services provision documentation

UNINTERRUPTIBLE POWER SUPPLY

— APPLICATIONS : IT, SMB

Series	Model	SKU	Power	Features	Communication	Equipment War.	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	Extended warranty			
											to 3 years	to 5 years		
X3 EX LCD USB FR/SCHUKO : Tower UPS - Line Interactive Technology with voltage regulation system														
	X3 EX 500 LCD USB FR/SCHUKO	65965	500 VA	2 FR/SCHUKO backup outlets RJ11/45 (In/Out) LCD Display	USB Port Software : InfoPower	120 000 €	3 years	287 x 100 x 142	3,95	4	-	62528		
	X3 EX 650 LCD USB FR/SCHUKO	65966	650 VA			120 000 €	3 years		4,25	4				
	X3 EX 800 LCD USB FR/SCHUKO	65967	800 VA			120 000 €	3 years		4,9	4				
	X3 EX 1000 LCD USB FR/SCHUKO	65968	1000 VA			120 000 €	3 years		5,2	4				
	X3 EX 1200 LCD USB FR/SCHUKO	65969	1200 VA	4 FR/SCHUKO backup outlets RJ11/45 (In/Out) LCD Display		150 000 €	3 years	350 x 146 x 160	8	1			-	62529
	X3 EX 1600 LCD USB FR/SCHUKO	65970	1600 VA			150 000 €	3 years	397 x 145 x 205	11,1	1				
	X3 EX 2000 LCD USB FR/SCHUKO	65971	2000 VA			150 000 €	3 years		12,5	1				
	X3 EX 3000 LCD USB FR/SCHUKO	66080	3000 VA			150 000 €	3 years	495 x 150 x 250	25	1				

— APPLICATIONS : IT, SMB

Series	Model	SKU	Power	Features	Communication	Equipment War.	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	Extended warranty			
											to 3 years	to 5 years		
X4 RT : Versatile UPS (Tower/rack) - Line Interactive High Frequency Technology with voltage regulation system														
	X4 650 RT	65285	650 VA	4 FR backup outlets + 1 FR surge-protected outlet RJ11 (In/Out) LCD display	USB Port Software : InfoPower	-	2 years	100 x 206 x 235	4,2	4	62511	62527		
	X4 850 RT	65286	850 VA			-	2 years		4,6	4	62512	62528		
<i>Provide a suitable cabinet for the depth (W/D) of the UPS.</i>														
X4 RM plus : Rackable-mounted UPS (Tower/rack) - Line Interactive Technology with voltage regulation system														
	X4 600 RM Plus	66061	600 VA	4 IEC outlets + 2 FR/SCHUKO backup outlets RJ45 (In/Out) LCD display	USB Port Software : InfoPower	-	2 years	230 x 440 x 88 (2U)	6,5	1	62512	62528		
	X4 800 RM Plus	66062	800 VA			-	2 years		7,7	1				
	X4 1000 RM Plus	66063	1000 VA	8 IEC outlets + 2 FR/SCHUKO backup outlets RJ45 (In/Out) LCD display		-	2 years	300 x 440 x 88 (2U)	11,3	1			62515	62531
	X4 2000 RM Plus	66064	2000 VA	8 IEC outlets + 2 FR/SCHUKO backup outlets RJ45 (In/Out) LCD display		-	2 years	300 x 440 x 88 (2U)	13,1	1			62517	62533
	X4 3000 RM Plus	66065	3000 VA	8 IEC outlets + 2 FR/SCHUKO backup outlets RJ45 (In/Out) LCD display		-	2 years	472 x 440 x 88 (2U)	22,4	1			62520	62536
<i>Make sur to provide suitable cabinet for the depth (D) of the UPS.</i>														
X4 RT : Associated accessory														
	Kit Rack 3U X4 RT	61437	-	Allows integration into a server cabinet	-	-	2 years	235 x 455 x 133 (3U)	2	1	-	-		
X4 RM Plus : Associated accessory														
	Kit Rack	61429	-	Fixing reinforcement in a patch cabinet	-	-	2 years	78.5 x 3.5 x 4.5	1,4	1	-	-		



UNINTERRUPTIBLE POWER SUPPLY

— APPLICATIONS : CORPORATE NETWORKS, TERTIARY SECTOR

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	Extended warranty		
										to 3 years	to 5 years	
E2 LCD : UPS - On Line Performance Technology												
	E2 LCD 600	65348	600 VA	4 IEC backup outlets RJ11/45 (In/Out) LCD display	USB Port Software : InfoPower	3 years	330 x 100 x 145	5,2	4		62528	
	E2 LCD 800	65349	800 VA			3 years		6	4			
	E2 LCD 1000	65350	1000 VA			3 years		350 x 146 x 160	9			1
	E2 LCD 1500	65351	1500 VA	6 IEC backup outlets RJ11/45 (In/Out) LCD display	USB & RS 232 Ports Software : InfoPower Optional : External SNMP I Pro Agent RS 232	3 years	397 x 146 x 205	11,6	1			62531
	E2 LCD 2000	65352	2000 VA			3 years		12,3	1			62533
E3 Live : Versatile UPS (Tower and/or Rack) - On Line Performance Technology												
	E3 Live 500 RM	66088	500 VA	4 IEC backup outlets 10A	USB & RS 232 Ports EPO Slot Optional : SNMP & Dry Contact Card Software : InfoPower	3 years	230 x 433 x 44 (1U)	7,6	1		62528	
	E3 Live 750 RM	66089	750 VA			3 years		8,6	1			
	E3 Live 1000 RM	66090	1000 VA			3 years		389 x 433 x 44 (1U)	14,2			1
	E3 Live 1500 RM	66091	1500 VA	3 years	16,2	1	62533					
	E3 Live 2200 RT	66092	2200 VA	4 IEC backup outlets 10A RJ45 (In/Out) LCD display	3 years	430 x 438 x 88 (2U)	16,7	1	62536			
	E3 Live 3000 RT	66093	3000 VA	8 IEC backup outlets 10A +1 IEC backup outlet 16A RJ45 (In/Out) LCD display	3 years		21,8	1				
E3 Performance : Versatile UPS (Tower/Rack) - On Line Performance Technology												
	E3 Performance 800 RT	67023	800 VA	8 IEC backup outlets 10A (4 standard + 4 programmable) RJ11/45 (In/Out) LCD display External battery connector	USB & RS 232 Ports EPO Slot Software : InfoPower Optional : SNMP & Dry Contact Card	3 years	425 x 438 x 88 (2U)	12,9	1		62531	
	E3 Performance 1100 RT	67024	1100 VA			3 years		13,4	1			
	E3 Performance 1500 RT	67025	1500 VA			3 years		525 x 438 x 88 (2U)	19,5			1
	E3 Performance 2000 RT	67026	2000 VA	8 IEC backup outlets 10A (4 standard + 4 programmable) RJ11/45 (In/Out) LCD display External battery connector	3 years	525 x 438 x 88 (2U)	21,5	1	62535			
	E3 Performance 2500 RT	67027	2500 VA	8 IEC backup outlets 10A (4 standard + 4 programmable) +1 IEC backup outlet 16A RJ11/45 (In/Out) LCD display	3 years		645 x 438 x 88 (2U)	26	1			62536
	E3 Performance 3000 RT	67028	3000 VA	External battery connector	3 years	645 x 438 x 88 (2U)	29,3	1				
	E3 Performance 5000 RT	67035	5000 VA	6 IEC backup outlets 10A (3 standard + 3 programmable) +1 IEC backup outlet 16A RJ11/45 (In/Out) LCD display External battery connector Output terminal block	3 years	645 x 438 x 88 (2U)	39,8	1	62538			
Make sur to provide suitable cabinet for the depth (D) of the UPS.												
E3 Performance : Backup modules - Extended autonomy up to 30 minutes and more depending on the connected load.												
	BM E3 Perf 0,8k AB24 R	67401	-	Compatible with E3 Performance 800k	24 Vdc Connector	2 years	515 x 440 x 88 (2U)	19,1	1			
	BM E3P E7 1k AC24 R	67402	-	Compatible with E3 Performance 1.1k	24 Vdc Connector	2 years		20,6	1			
	BM E3 Perf 1,5k CB48 R	67405	-	Compatible with E3 Performance 1.5k	48 Vdc Connector	2 years		20,87	1			
	BM E3P E7 2k CC48 R	67406	-	Compatible with E3 Performance 2k	48 Vdc Connector	2 years	30	1				
	BM E3 Perf 2,5k DB72 R	67408	-	Compatible with E3 Performance 2.5k	72 Vdc Connector	2 years	635 x 440 x 88 (2U)	38,8	1			
	BM E3P E7 3k DC72 R	67409	-	Compatible with E3 Performance 3k /5k	72 Vdc Connector	2 years		43,3	1			
Make sur to provide suitable cabinet for the depth (D) of the backup module.												



UNINTERRUPTIBLE POWER SUPPLY

— APPLICATIONS : CORPORATE NETWORKS, SENSITIVE APPLICATIONS

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	Extended warranty			
										to 3 years	to 5 years		
E3 Pro : Versatile UPS (Tower/Rack) - On Line Double Conversion Technology.													
	E3 Pro 1000 RM (1U)	67314	1000 VA	3 IEC backup outlets 10A : 1 standard outlet + 2 programmable outlets LED	USB & RS 232 Ports Software : InfoPower Optional : SNMP & Dry Contact Card	3 years	477 x 438 x 44 (1U)	12.7	1	62533	62536		
	E3 Pro 1000 RT	67308	1000 VA	3 IEC outlets Smart and adjustable charger up to 3.5A External battery connector LCD display		3 years	310 x 438 x 88 (2U)	12.7	1				
	E3 Pro 2000 RT	67309	2000 VA	4 IEC outlets Smart and adjustable charger up to 3.5A External battery connector LCD display		3 years	410 x 438 x 88 (2U)	19	1				
	E3 Pro 3000 RT	67310	3000 VA	4 IEC outlets + output terminal block Smart and adjustable charger up to 3.5A External battery connector LCD display		3 years	630 x 438 x 88 (2U)	29.3	1				
	E3 Pro 5000 RT	67319	5000 VA	Terminal block Smart and adjustable charger up to 6A External battery connector LCD display	USB & RS 232 Ports EPO slot Software : InfoPower Optional : SNMP & Dry Contact Card	2 years	530 x 438 x 88 (2U) + 740 x 438 x 88 [2U]*	15+55*	1	62525	62538		
	<i>Delivered with its external backup module (67187)</i>												
	E3 Pro 6000 RT	67320	6000 VA	Terminal block Smart and adjustable charger up to 6A External battery connector LCD display	USB & RS 232 Ports EPO slot Software : InfoPower Optional : SNMP & Dry Contact Card	2 years	530 x 438 x 88 (2U) + 740 x 438 x 88 [2U]*	15+47*	1				
	<i>Delivered with its external backup module (67187)</i>												
E3 Pro 10k RT	67321	10000 VA	Terminal block Smart and adjustable charger up to 6A External battery connector LCD display	USB & RS 232 Ports EPO slot Software : InfoPower Optional : SNMP & Dry Contact Card	2 years	605 x 438 x 133 (3U) + 630 x 438 x 133 [3U]*	18+63*	1	62526	62539			
<i>Delivered with its external backup module (67189)</i>													
* Battery cabinet													
Make sur to provide suitable cabinet for the depth (D) of the UPS and backup module.													
E3 Pro : Backup modules - Extended autonomy up to 30 minutes and more depending on the connected load.													
	BM E3P E7 1k AC24 R	67402	-	Compatible with E3 Pro 1k RT	24 Vdc Connector	2 years	515 x 440 x 88 (2U)	20,6	1	-	-		
	BM E3P E7 1k CC24 R	67403	-	Compatible with E3 Pro 1k RT	24 Vdc Connector	2 years		30	1				
	BM E3P E7 2k CC48 R	67406	-	Compatible with E3 Pro 2k RT	48 Vdc Connector	2 years		30	1				
	BM E3P E7 3k DC72 R	67409	-	Compatible with E3 Pro 3k RT	72 Vdc Connector	2 years	635 x 440 x 88 (2U)	43,3	1				
	BM E3Pro E7 5-6k EC192 R	67187	-	Compatible with E3 Pro 5/6k RT	192 Vdc Connector	2 years	740 x 438 x 88 (2U)	47	1				
	BM E3Pro E7 8-10k FC240 R	67189	-	Compatible with E3 Pro 10k RT	240 Vdc Connector	2 years	630 x 438 x 133 (3U)	63	1				
Make sur to provide suitable cabinet for the depth (D) of the backup module.													
E3 Live : Associated accessories													
	Kit Rack E3 Live RM (1U)	61810	-	Fixing reinforcement in a patch cabinet for E3 Live RM UPS (1U)	-	2 years	-	-	1	-	-		
	Kit Rack E3 Live RT (2U)	61811	-	Fixing reinforcement in a patch cabinet for E3 Live RM UPS (2U)	-	2 years	-	-	1				
	SNMP II Pro Agent E3 Live	61812	-	SNMP Agent card for E3 Live UPS	-	2 years	-	-	1				
	Dry Contact Card AS400 9PIN E3 Live	61809	-	AS400 Dry Contact Card	-	2 years	-	-	1				
E3 Performance / Pro : Associated accessories													
	Kit Rack	61429	-	Fixing reinforcement in a patch cabinet	-	2 years	78.5 x 3.5 x 4.5	1.45	1	-	-		
	SNMP I Pro Agent (Network Management)	61156	-	SNMP Agent card for UPS equipped with a SNMP slot	-	2 years	-	-	1				
	External USB SNMP Agent (Network Management)	61823	-	DY 630 USB SNMP Agent for all products equipped with a USB port	-	2 years	-	-	1				
	External SNMP I Pro Agent RS 232 (Network Management)	61830	-	SNMP Agent for all products equipped with a RS 232 port	-	2 years	-	-	1				
	SNMP Agent vm MiniSlot (Virtual Environment Network Management)	61142	-	vmWare®-Ready SNMP Agent for virtual network CS141 Minislot (compatible with vmWare® etc.) + 1 RCCMD license	-	2 years	-	-	1				
	RCCMD license for virtual server management	61143	-	1 RCCMD Licence (1 per additional network environment) compatible with SNMP agent vm MiniSlot (ref. 61142)	-	2 years	-	-	1				
	Temperature & Humidity Probe - EMD	61452	-	Temperature and humidity detector to be connected to the SNMP I Pro agent	-	2 years	-	-	1				
	Temperature Probe CS141 MINI	61822	-	Temperature detector to be connected to the SNMP agent vm MiniSlot	-	2 years	-	-	1				
	Temperature & Humidity Probe CS141 MINI	61839	-	Temperature and humidity detector to be connected to the SNMP agent vm MiniSlot	-	2 years	-	-	1				
	Dry Contact Card AS400 9PIN	61454	-	AS400 Embeddable Dry Contact Card	-	2 years	-	-	1				
	Modbus Card	61439	-	Embeddable card - Modbus RTU Protocol	-	2 years	-	-	1				
	BME 1 IEC RM	61442	1 to 3 kVA	19" External bypass-PDU RM for E3 Perf / Pro from 1 to 3kVA with IEC outlets	-	2 years	88 x 440 x 60	1,5	1				
BME 1 FR RM	61443	1 to 3 kVA	19" External bypass-PDU RM for E3 Perf / Pro from 1 to 3kVA with FR outlets	-	2 years	88 x 440 x 60	1,5	1					

SINGLE-PHASE INPUT / SINGLE-PHASE OUTPUT UPS



⚠ Make sure to provide suitable cabinet for the depth (D) of

UNINTERRUPTIBLE POWER SUPPLY

— APPLICATIONS : CORPORATE NETWORKS, TERTIARY SECTOR

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	Extended warranty	
										to 3 years	to 5 years
E4 VALUE - UPS - On Line Double Conversion High Frequency Technology											
	E4 VALUE 1000	67417	1000 VA	3 IEC Backup outlets LED Display	RS 232 Port InfoPower Software Optional : External SNMP Agent	2 years	220 x 145 x 282	8,6	1	62517	62533
	E4 VALUE 1500	67425	1500 VA	4 IEC Backup outlets LED Display		2 years	235 x 145 x 397	16,1	1	62519	62535
	E4 VALUE 2000	67418	2000 VA	4 IEC Backup outlets LED Display		2 years	235 x 145 x 397	16,1	1		
	E4 VALUE 3000	67419	3000 VA	4 IEC Backup outlets + output terminal block LED Display		2 years	335 x 190 x 421	25,2	1	62520	62536
	E4 VALUE 4000	67426	4000 VA	Input/output terminals LCD display	USB & RS 232 Ports Software : InfoPower Optional : SNMP card	2 years	388 x 190 x 573	46	1	62525	62538
	E4 VALUE 5000	67420	5000 VA	Input/output terminals LCD display		2 years	369 x 190 x 573	60	1		
E4 VALUE + 6000	67656	6000 VA	Input/output terminals LCD display Manual Bypass Maintenance	2 years		369 x 190 x 688	60	1			
E4 VALUE + 10K	67657	10 kVA		2 years	460 x 190 x 688	75	1	62526	62539		

— APPLICATIONS : NETWORKS AND SENSITIVE APPLICATIONS, INDUSTRIAL SECTORS

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	Extended warranty	
										to 3 years	to 5 years
E4 LCD Pro - UPS - On Line Double Conversion High Frequency Technology											
	E4 LCD Pro 1000	67230	1000 VA	3 IEC Backup outlets External battery connector LCD display	USB & RS 232 Ports InfoPower Optional : SNMP, Modbus card, Dry Contact Card	2 years	282 x 145 x 220	9,4	1	62517	62533
	E4 LCD Pro 1500	67274	1500 VA	4 IEC Backup outlets External battery connector LCD display		2 years	397 x 145 x 220	17	1	62519	62535
	E4 LCD Pro 2000	67231	2000 VA	4 IEC Backup outlets External battery connector LCD display		2 years	397 x 145 x 200	17	1		
	E4 LCD Pro 3000	67232	3000 VA	4 IEC Backup outlets + output terminal block External battery connector LCD display		2 years	421 x 190 x 318	26,9	1	62520	62536
	E4 Pro One 5000	67629	5000 VA	Input/output terminals High power factor (1) External battery connector LCD Display Manual Bypass Maintenance Parallel Configuration (optional)	USB & RS 232 Ports EPO Slot Software : InfoPower Optional : SNMP, Modbus card, Dry Contact Card	2 years	369 x 190 x 688	60	1	62525	62538
	E4 Pro One 6000	67630	6000 VA			2 years	369 x 190 x 688	60	1		
	E4 Pro One 8000	67631	8000 VA			2 years	442 x 190 x 688	75	1	62526	62539
	E4 Pro One 10k	67632	10k VA			2 years	442 x 190 x 688	75	1		


Value




LCD Pro




Pro ONE




ONE RT



UNINTERRUPTIBLE POWER SUPPLY

— APPLICATIONS : CORPORATE NETWORKS, SENSITIVE EQUIPMENTS

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	Extended warranty	
										to 3 years	to 5 years
E4 LCD Pro / E4 Pro One : Backup modules - Extended autonomy up to 25 minutes and more depending on the connected load											
B	BM E4 LCD Pro 1k BC24 T	67277	-	Compatible with E4 Pro 1k	24 Vdc connector	2 years	397 x 145 x 220	22	1		
	BM E4 LCD Pro 1,5-2k CC48 T	67279	-	Compatible with E4 Pro 1,5/2k	48 Vdc connector	2 years		27	1		
	BM E4 LCDPro 3k DC72 T	67281	-	Compatible with E4 Pro 3k	72 Vdc connector	2 years	421 x 190 x 318	42	1		
	BM E4 Pro One 5-6k GC192 T	67283	-	Compatible with E4 Pro One 5/6k	192 Vdc connector	2 years	442 x 190 x 688	95	1		
	BM E4 Pro One &TM 8-10k HC240 T	67284	-	Compatible with E4 Pro One 8/10k	240 Vdc connector	2 years		115	1		
E4 Value / E4 LCD Pro / E4 Pro One : Associated accessories											
A	SNMP I Pro Agent (Network Management)	61156	-	SNMP Agent card for UPS equipped with a SNMP slot	-	2 years	-	-	1		
	External SNMP I Pro Agent RS 232 (Network Management)	61830	-	SNMP Agent for all products equipped with a RS 232 port	-	2 years	-	-	1		
	External USB SNMP Agent (Network Management)	61823	-	DY 630 USB SNMP Agent for all products equipped with a USB port	-	2 years	-	-	1		
	SNMP Agent vm MiniSlot (Virtual Environment Network Management)	61142	-	vmWare®-ready SNMP Agent for virtual network CS141 Minislot (compatible with vmWare® etc.) + 1 RCCMD license	-	2 years	-	-	1		
	RCCMD license for virtual server management	61143	-	1 RCCMD Licence (1 per additional network environment) compatible with SNMP agent vm MiniSlot (ref. 61142)	-	2 years	-	-	1		
	Temperature & Humidity Probe - EMD	61452	-	Temperature and humidity detector to be connected to the SNMP I Pro agent	-	2 years	-	-	1		
	Temperature Probe CS141 MINI	61822	-	Temperature detector to be connected to the SNMP agent vm MiniSlot	-	2 years	-	-	1		
	Temperature & Humidity Probe CS141 MINI	61839	-	Temperature and humidity detector to be connected to the SNMP agent vm MiniSlot	-	2 years	-	-	1		
	Dry Contact Card AS400 9PIN	61454	-	AS400 Embeddable Dry Contact Card	-	2 years	-	-	1		
	Modbus Card	61439	-	Embeddable card - Modbus RTU Protocol	-	2 years	-	-	1		
	BME 1 IEC	61440	1 to 3 kVA	External bypass Tower-PDU for E4 Pro from 1 to 3KVA with IEC outlets	-	2 years	180 x 160 x 60	1,3	1		
	BME 1 FR	61441	1 to 3 kVA	External bypass Tower-PDU for E4 Pro from 1 to 3KVA with FR outlets	-	2 years	180 x 200 x 60	1,3	1		
	Parallel Configuration Kit E4 Pro One	67910	-	Cable kit for a parallel configuration to be installed before delivery	-	2 years	-	-	1		

— APPLICATIONS : CORPORATE NETWORKS, TERTIARY SECTOR AND SENSITIVE EQUIPMENTS

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	Extended warranty	
										to 3 years	to 5 years
E7 One RT : 19" Rack-mountable & Versatile (Tower/Rack) Paralleling Capability and Redundant UPS											
On Line Double Conversion High Frequency Technology											
E7 ONE RT	E7 One 1000 RT	67333	1000 VA	High power factor (1) Powerful built-in battery charger Programmable sockets External battery connector LCD display	USB & RS 232 Ports EPO Slot Software : InfoPower Optional : SNMP card, Dry Contact Card, Modbus card	2 years	410 x 438 x 88 (2U)	11,6	1	62517	62533
	E7 One 1500 RT	67334	1500 VA			2 years	410 x 438 x 88 (2U)	15,5	1	62519	62535
	E7 One 2000 RT	67335	2000 VA			2 years	510 x 438 x 88 (2U)	19,5	1	62520	62536
	E7 One 3000 RT	67336	3000 VA			2 years	630 x 438 x 88 (2U)	27,5	1	62520	62536
	E7 One 5000 RT	67346	5000 VA	Input/output terminals High power factor (1) External battery connector LCD Display Parallel Configuration (optional)	USB & RS 232 Ports EPO Slot Software : InfoPower Optional : SNMP card, Dry Contact Card, Modbus card	2 years	610 x 438 x 88 (2U) + 740 x 438 x 88 (2U)	17 + 47*	1	62525	62538
	<i>Delivered with its external backup module (67187)</i>										
	E7 One 6000 RT	67337	6000 VA	Input/output terminals High power factor (1) External battery connector LCD Display Parallel Configuration (optional)	USB & RS 232 Ports EPO Slot Logiciel : InfoPower En option : carte SNMP, carte contacts secs, carte Modbus	2 years	610 x 438 x 88 (2U) + 740 x 438 x 88 (2U)	17 + 47*	1	62526	62539
	<i>Delivered with its external backup module (67187)</i>										
	E7 One 8000 RT	67347	8 000 VA	Input/output terminals High power factor (1) External battery connector LCD Display Parallel Configuration (optional)	USB & RS 232 Ports EPO Slot Software : InfoPower Optional : SNMP card, Dry Contact Card, Modbus card	2 years	610 x 438 x 88 (2U) 630 x 438 x 133 (3U)*	20 + 63*	1	62526	62539
	<i>Delivered with its external backup module (67189)</i>										
E7 One 10k RT	67338	10 000 VA	Input/output terminals High power factor (1) External battery connector LCD Display Parallel Configuration (optional)	USB & RS 232 Ports EPO Slot Software : InfoPower Optional : SNMP card, Dry Contact Card, Modbus card	2 years	610 x 438 x 88 (2U) 630 x 438 x 133 (3U)*	20 + 63*	1	62526	62539	
<i>Delivered with its external backup module (67189)</i>											
* Battery cabinet											
Make sur to provide suitable cabinet for the depth (D) of the UPS and backup module.											

UNINTERRUPTIBLE POWER SUPPLY

— APPLICATIONS : CORPORATE NETWORKS, TERTIARY SECTOR AND SENSITIVE APPLICATIONS

SINGLE-PHASE INPUT / SINGLE-PHASE OUTPUT UPS

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	Extended warranty
E7 One RT : Additional autonomy modules										
B	BM E3P E7 1k AC24 R	67402	-	Compatible with E7 One 1000 RT	24 Vdc connector	2 years	515 x 440 x 88 (2U)	20,6	1	
	BM E3P E7 1k CC24 R	67403	-	Compatible with E7 One 1000 RT		2 years		30	1	
	BM E3P E7 2k CC48 R	67406	-	Compatible with E7 One 2000 RT	48 Vdc connector	2 years		30	1	
	BM E3P E7 3k DC72 R	67409	-	Compatible with E7 One 3000 RT	72 Vdc connector	2 years	635 x 440 x 88 (2U)	43,3	1	
	BM E3Pro E7 5-6k EC192 R	67187	-	Compatible with E7 One 5000, 6000 RT	192 Vdc connector	2 years	740 x 438 x 88 (2U)	47	1	
	BM E3Pro E7 8-10k FC240 R	67189	-	Compatible with E7 One 8000, 10k RT	240 Vdc connector	2 years	630 x 438 x 133 (3U)	63	1	
Make sur to provide suitable cabinet for the depth (D) of the UPS autonomy module.										
E7 One RT : Associated accessories										
A	Kit Rack	61429	-	Fixing reinforcement in a patch cabinet	-	2 years	78.5 x 3.5 x 4.5	1,4	1	
	SNMP I Pro Agent (Network Management)	61156	-	SNMP Agent card for UPS equipped with a SNMP slot	-	2 years	-	-	1	
	External USB SNMP Agent (Network Management)	61823	-	DY 630 USB SNMP Agent for all products equipped with a USB port	-	2 years	-	-	1	
	External SNMP I Pro Agent RS 232 (Network Management)	61830	-	SNMP Agent for all products equipped with a RS 232 port	-	2 years	-	-	1	
	SNMP Agent vm MiniSlot (Virtual Environment Network Management)	61142	-	vmWare®-ready SNMP Agent for virtual network CS141 Minislot (compatible with vmWare® etc.) + 1 RCCMD license	-	2 years	-	-	1	
	RCCMD license for virtual server management	61143	-	1 RCCMD Licence (1 per additional network environment) compatible with SNMP agent vm MiniSlot (ref. 61142)	-	2 years	-	-	1	
	Temperature & Humidity Probe - EMD	61452	-	Temperature and humidity detector to be connected to the SNMP I Pro agent	-	2 years	-	-	1	
	Temperature Probe CS141 MINI	61822	-	Temperature detector to be connected to the SNMP agent vm MiniSlot	-	2 years	-	-	1	
	Temperature & Humidity Probe CS141 MINI	61839	-	Temperature and humidity detector to be connected to the SNMP agent vm MiniSlot	-	2 years	-	-	1	
	Dry Contact Card AS400 9PIN	61454	-	AS400 Dry Contact Card	-	2 years	-	-	1	
	Modbus Card	61439	-	Embeddable card - Modbus RTU Protocol	-	2 years	-	-	1	
	BME 1 IEC RM	61442	1 to 3 kVA	19" External bypass-PDU RM for E3 Perf / Pro from 1 to 3kVA with IEC outlets	-	2 years	88 x 440 x 60	-	1	
	BME 1 FR RM	61443	1 to 3 kVA	19" External bypass-PDU RM for E3 Perf / Pro from 1 to 3kVA with FR outlets	-	2 years	88 x 440 x 60	-	1	
	BME 2 RM	61444	5 to 10 kVA	19" External bypass for E7 One RT from 5 to 10kVA	-	2 years	165 x 440 x 88 (2U)	3	1	
Parallel Configuration Kit E7 One 5K/10K RT	67910	-	Cable kit for a parallel configuration to be installed before delivery	-	2 years	-	-	1		

UPS SYSTEMS

— APPLICATIONS : SENSITIVE NETWORKS AND APPLICATIONS, INDUSTRIAL SECTORS

THREE-PHASE INPUT / SINGLE-PHASE OUTPUT UPS

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	Maintenance contracts
E4 LCD Pro TM - On Line Double Conversion High Frequency Technology										
4 LCD Pro	E4 LCD Pro 10k TM	67508	10k VA	Input/output terminals External battery connector LCD Display Manual Bypass Maintenance	USB & RS 232 Ports EPO Slot Software : InfoPower Optional : SNMP card, Dry Contact Card, Modbus card	2 years	419 x 190 x 688	65,4	1	Subscribe to an Infosec maintenance contract ! Discover all Infosec services in our dedicated documentation !
	E4 LCD Pro 15k TM	67509	15k VA			2 years	442 x 190 x 688	76,4	1	
	E4 LCD Pro 20k TM	67517	20k VA			2 years	815 x 250 x 826	126,6	1	
These UPS also exist in an extended autonomy «S» version - Consult us										
E4 LCD Pro TM : Additional backup modules										
B	BM E4 Pro One & TM 8-10k HC240 T	67284	-	Compatible with E4 LCD Pro 10k TM	240 Vdc connector	2 years	442 x 190 x 688	115	1	
	BM E4LCDPro 15kTM FC240 T	67542	-	Compatible with E4 LCD Pro 15k TM	240 Vdc connector	2 years	442 x 190 x 688	72	1	
	BM E4LCDPro 20kTM GC196 T	67476	-	Compatible with E4 LCD Pro 20k TM	196 Vdc connector	2 years	442 x 190 x 688	103,8	1	



UNINTERRUPTIBLE POWER SUPPLY

— APPLICATIONS : SENSITIVE NETWORKS AND APPLICATIONS, INDUSTRIAL SECTORS

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	Maintenance contracts
E4 LCD Pro TM : Associated accessories										
	SNMP I Pro Agent (Network Management)	61156	-	SNMP Agent card for UPS equipped with a SNMP slot	-	2 years	-	-	1	
	External SNMP I Pro Agent RS 232 (Network Management)	61830	-	SNMP Agent for all products equipped with a RS 232 port	-	2 years	-	-	1	
	SNMP Agent vm MiniSlot (Virtual Environment Network Management)	61142	-	vmWare®-ready SNMP Agent for virtual network CS141 Minislot (compatible with vmWare® etc.) + 1 RCCMD license	-	2 years	-	-	1	
	RCCMD license for virtual server management	61143	-	1 RCCMD Licence (1 per additional network environment) compatible with SNMP agent vm MiniSlot (ref. 61142)	-	2 years	-	-	1	
	Temperature & Humidity Probe - EMD	61452	-	Temperature and humidity detector to be connected to the SNMP I Pro agent	-	2 years	-	-	1	
	Temperature Probe CS141 MINI	61822	-	Temperature detector to be connected to the SNMP agent vm MiniSlot	-	2 years	-	-	1	
	Temperature & Humidity Probe CS141 MINI	61839	-	Temperature and humidity detector to be connected to the SNMP agent vm MiniSlot	-	2 years	-	-	1	
	Dry Contact Card AS400 9PIN	61454	-	AS400 Embeddable Dry Contact Card	-	2 years	-	-	1	
	Modbus Card	61439	-	Embeddable card - Modbus RTU Protocol	-	2 years	-	-	1	
E6 LCD TM RM : 19" Rack-mountable paralleling capability and redundant UPS (three/single) - On Line Double Conversion High Frequency Technology										
	E6 LCD 20k TM RM	67324	20 kVA	Input/output terminals External battery connector LCD Display Optional : parallel configuration card	USB & RS 232 Ports EPO Slot Software : InfoPower Optional : SNMP card, Dry Contact Card, Modbus card	1 year	745 x 440 x 266 (6U) 2 x + 630 x 438 x 133 (3U)*	45 + 2 x 63*	1	 Subscribe to an Infosec maintenance contract ! Discover all Infosec services in our dedicated documentation !
		*Battery cabinet The E6 LCD TM RM range can be configured as single/single on request Make sur to provide suitable cabinet for the depth (D) of the UPS and backup module.							Delivered with its external backup module (67189)	
E6 LCD TM RM : Associated accessories										
	Kit Rack	61429	-	Fixing reinforcement in a patch cabinet	-	2 years	78.5 x 3.5 x 4.5	1,4	1	
	SNMP I Pro Agent (Network Management)	61156	-	SNMP Agent card for UPS equipped with a SNMP slot	-	2 years	-	-	1	
	SNMP Agent vm MiniSlot (Virtual Environment Network Management)	61142	-	vmWare®-ready SNMP Agent for virtual network CS141 Minislot (compatible with vmWare® etc.) + 1 RCCMD license	-	2 years	-	-	1	
	Dry Contact Card AS400 9PIN	61454	-	AS400 Dry Contact Card	-	2 years	-	-	1	
	BME 3 TM RM	61458	15/20kVA	19" External bypass for E6 LCD TM RM 15-20KVA	-	2 years	196 x 438 x 88 (2U)	3	1	
	Parallel Configuration Kit E6 TM RM 15 and 20k	61463	-	Kit to be installed before delivery	-	2 years	-	-	1	

THREE-PHASE INPUT / SINGLE-PHASE OUTPUT UPS

UNINTERRUPTIBLE POWER SUPPLY

— APPLICATIONS : SENSITIVE NETWORKS AND APPLICATIONS, INDUSTRIAL SECTORS

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	Maintenance contracts
E4 Evolution II TT - Paralleling capability and redundant UPS (three/three) - On Line Double Conversion High Frequency Technology										
	E4 Evolution II 100k TT S	67555	100k VA	Input/output terminals High power factor (0.9) Double power supply 10" LCD touch screen Parallel connection of up to 2 UPS with battery modules in common Manual Bypass Maintenance Simplified maintenance per module	USB & RS 232 Ports EPO Slot Software : InfoPower Options : SNMP card, Dry Contact Card, Modbus card	1 year	940 x 567 x 1015	207 *	1	 Subscribe to an Infosec maintenance contract ! Discover all Infosec services in our dedicated documentation !
				The SB versions are configured for extended autonomies - Consult us The S models are UPS without internal batteries but equipped with a powerful charger designed for the addition of extended autonomy modules. * weight without batteries						
E4 Evolution II + TT HD - Solution for elevators equipped with regenerative drive system and motor braking system On Line Double Conversion High Frequency Technology										
	E4 Evolution II + 30k TT HD AN10*	67635	30k VA	Input/output terminals High power factor (1) LCD display Reinjected current absorption bank (Energy Box) Manual Bypass Maintenance Simplified maintenance per module	USB & RS 232 Ports EPO Slot Software : InfoPower Optional : SNMP card, Dry Contact Card, Modbus card	1 year	815 x 300 x 1000 + 815 x 250 x 826	60 + 208	1	 Subscribe to an Infosec maintenance contract ! Discover all Infosec services in our dedicated documentation !
				* AN 10 = Nominal Autonomy (10 min) Delivered with its external backup module (67479)						

THREE-PHASE INPUT / THREE-PHASE OUTPUT UPS

UNINTERRUPTIBLE POWER SUPPLY

APPLICATIONS : SENSITIVE NETWORKS AND APPLICATIONS, INDUSTRIAL SECTORS

THREE-PHASE INPUT / THREE-PHASE OUTPUT UPS

THREE-PHASE INPUT / SINGLE-PHASE OUTPUT UPS

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxxwxh (mm)	Weight (kg)	Per Outer	Maintenance contracts			
MST : Paralleling capability and redundant UPS (three/three) - On Line Double Conversion High Frequency Technology													
	MST 10k SB	67670	10 kVA	Input/output terminals High power factor (1) Double power supply LCD touch screen (5" or 7" depending on model) Parallel connection (up to 4 or 6 UPS with battery modules in common, depending on model) Manual Bypass Maintenance	USB & RS 232 Ports EPO Slot Software : InfoPower Optional : SNMP card, Dry contact card (100 to 200 kVA models), Modbus card	1 year	627 x 250 x 826	41	1	 Subscribe to an Infosec maintenance contract ! Discover all Infosec services in our dedicated documentation !			
	MST 10k AN10	67658	10 kVA			1 year	627 x 250 x 826	105	1				
	MST 10k AN30*	67678	10 kVA			1 year	627 x 250 x 826	165	1				
	Delivered with its internal battery kit (67619)												
	MST 15k SB	67668	15 kVA			1 year	627 x 250 x 826	45	1				
	MST 15k AN10	67659	15 kVA			1 year	627 x 250 x 826	125	1				
	MST 15k AN30*	67679	15 kVA			1 year	627 x 250 x 826 + 830 x 250 x 576	125+128	1				
	Delivered with its external autonomy module (67733)												
	MST 20k SB	67669	20 kVA			1 year	627 x 250 x 826	45	1				
	MST 20k AN10	67660	20 kVA			1 year	627 x 250 x 826	125	1				
	MST 20k AN30*	67680	20 kVA			1 year	627 x 250 x 826 + 830 x 250 x 576	128+208	1				
	Delivered with its external autonomy module (67733)												
	MST 30k SB	67671	30 kVA			1 year	815 x 300 x 1000	78	1				
	MST 30k AN10	67661	30 kVA			1 year	815 x 300 x 1000	213	1				
	MST 30k AN20*	67681	30 kVA			1 year	815 x 300 x 1000 + 815 x 250 x 826	213+208	1				
	Delivered with its external autonomy module (67479)												
	MST 40k SB	67672	40 kVA			1 year	815 x 300 x 1000	80	1				
	MST 40k AN10	67662	40 kVA			1	815 x 300 x 1000	243	1				
	MST 40k AN20*	67682	40 kVA			1 year	815 x 300 x 1000 + 815 x 250 x 826	243+208	1				
	Delivered with its external autonomy module (67481)												
MST 60k S	67663	60 kVA	1 year	815 x 300 x 1000	87**0	1							
MST 80k S	67687	80 kVA	1 year	979 x 600 x 1600	250**0	1							
MST 100k S	67664	100 kVA	1 year	979 x 600 x 1600	250**0	1							
MST 120k S	67665	120 kVA	1 year	979 x 600 x 1600	250**0	1							
MST 150k S	67688	150 kVA	1 year	979 x 600 x 1600	309**0	1							
MST 180k S	67666	180 kVA	1 year	979 x 600 x 1600	309**0	1							
MST 200k S	67667	200 kVA	1 year	979 x 600 x 1600	311**0	1							
The SB versions are configured for extended autonomies - Consult us. The S models are UPS without internal batteries but equipped with a powerful charger designed for the addition of extended autonomy modules. The MST models from 10 to 20 kVA can be configured in three/single on request. * AN = Nominal Autonomy (for example AN20 = Nominal Autonomy 20 min) ** weight without batteries													

MST HD - Solution for elevators equipped with regenerative drive system and motor braking system												
On Line Double Conversion High Frequency Technology												
	MST 20k HV AN10 HD*	67686	20k VA	Input/output terminals High power factor (1) Reinject current absorption bank (HD Energy Box) LCD display Manual Bypass Maintenance Simplified maintenance per module	USB & RS 232 Ports EPO Slot Software : InfoPower Optional : SNMP card, Dry contact card (MST HD 60k S), Modbus card	1 year	627 x 250 x 826 + 980 x 580 x 285	125 + 21	1	 Subscribe to an Infosec maintenance contract ! Discover all Infosec services in our dedicated documentation !		
	Delivered with the external accessory MST HD Box (61820)											
	MST 30k HV AN10 HD*	67683	30k VA			1 year	815 x 300 x 1000 + 980 x 580 x 285	213 + 21	1			
	Delivered with the external accessory MST HD Box (61820)											
MST 40k HV AN10 HD*	67684	40k VA	1 year	815 x 300 x 1000 + 980 x 580 x 285	243 + 21	1						
Delivered with the external accessory MST HD Box (61820)												
MST 60k S HV HD	67685	60k VA	1 year	815 x 300 x 1000 + 980 x 580 x 285	87** + 21	1						
Delivered with the external accessory MST HD Box (61820)												
* AN10 = Nominal Autonomy (10 min) ** weight without batteries												

E4 Evolution II TT / MST : Associated accessories										
	SNMP I Pro Agent (Network Management)	61156	-	SNMP Agent card for UPS equipped with a SNMP slot	-	2 years	-	-	1	 Subscribe to an Infosec maintenance contract ! Discover all Infosec services in our dedicated documentation !
	External SNMP I Pro Agent RS 232 (Network Management)	61830	-	SNMP Agent for all products equipped with a RS 232 port	-	2 years	-	-	1	
	SNMP Agent vm MiniSlot (Virtual Environment Network Management)	61142	-	vmWare®-ready SNMP Agent for virtual network CS141 Minislot (compatible with vmWare® etc.) + 1 RCCMD license	-	2 years	-	-	1	
	RCCMD license for virtual server management	61143	-	1 RCCMD Licence (1 per additional network environment) compatible with SNMP agent vm MiniSlot (ref. 61142)	-	2 years	-	-	1	
	Temperature & Humidity Probe - EMD	61452	-	Temperature and humidity detector to be connected to the SNMP I Pro agent	-	2 years	-	-	1	
	Temperature Probe CS141 MINI	61822	-	Temperature detector to be connected to the SNMP agent vm MiniSlot	-	2 years	-	-	1	
	Temperature & Humidity Probe CS141 MINI	61839	-	Temperature and humidity detector to be connected to the SNMP agent vm MiniSlot	-	2 years	-	-	1	
	Dry Contact Card AS400 9PIN (except MST from 10 to 40 kVA)	61454	-	AS400 Embeddable Dry Contact Card	-	2 years	-	-	1	
	Modbus card	61439	-	Embeddable card - Modbus RTU Protocol	-	2 years	-	-	1	
	Parallel configuration cable MST 10/15/20kVA	67909	-	Cables for a parallel configuration to be installed before delivery	-	2 years	-	-	1	
	MST HD Box (for MST 20/30/40/60 kVA models)	61820	-	External accessory consisting of an integrated resistance bank	-	1 year	980 x 580 x 285	125 + 21	1	

UNINTERRUPTIBLE POWER SUPPLY

— APPLICATIONS : CRITICAL NETWORKS AND APPLICATIONS, DATA CENTERS

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer	
Mod3 : Paralleling capability and redundant UPS (three/three, three/single, single/single) - On Line Double Conversion High Frequency Technology										
Mod3 : Modular solution for single use in 19" rack format & versatile (Tower/Rack)										
Mod3	Mod3 C 10k TT	67725	10 kVA Power modules with connection kit	Redundant modular configuration Available in 3/3, 3/1, 1/1 Hot swappable power modules Input/output terminal blocks LCD display Batteries in separate cabinets	USB Port Software : InfoPower Optional : SNMP card, connection kit for models without connection kit (C), control module	1 year	678 x 418 x 129 [3U]	21	1	
	Mod3 10k TT	67726	10 kVA Power modules without connection kit			1 year	604 x 418 x 129 [3U]	20	1	
	Mod3 C 10k TM	67727	10 kVA Power modules with connection kit			1 year	678 x 418 x 129 [3U]	20,5	1	
	Mod3 10k TM	67728	10 kVA Power modules without connection kit			1 year	604 x 418 x 129 [3U]	18,5	1	
Mod3 : Modular solution for use in a pre-configured Mod3 rack cabinet (19U)										
B	Mod3 C 40/10 (19U) TT (max nb of installable power modules: 4* 10 kVA)	67729	10 to 40 kVA Per 10kVA power modules	Redundant modular configuration Available in 3/3, 3/1, 1/1 Hot swappable power modules Input/output terminal blocks 5,7" color LCD display Control modules	USB Port Software : InfoPower Optional : SNMP card, 10" LCD touch screen	1 year	875 x 443 x 840 [19U]	72*	1	
	Mod3 C 40/10 (19U) TT (max nb of installable power modules: 4* 10 kVA)	67730	10 to 40 kVA Per 10kVA power modules			1 year		72*	1	
* weight without batteries The 3/1 phase versions can be configured as 1/1 phase For any particular configuration and extended autonomy battery cabinets, please contact us										
Mod3 : Backup modules - Autonomy extension										
Power modules Mod3 for single use in 19" rack format & versatile (Tower/Rack)										
B	BM Mod3C EC192 R	67583	-	192V*/9Ah Autonomy module		1 year	678 x 418 x 129 [3U]	51	1	
	BM Mod3C FC240 R	67584	-	240V*/9Ah Autonomy module		1 year	678 x 418 x 129 [3U]	61	1	
	BM Mod3C GA384 R	67585	-	384V*/5Ah Autonomy module		1 year	678 x 418 x 129 [3U]	68,6	1	
	Mod3 Power module for use in a pre-configured Mod3 rack cabinet (19U)									
	BM Mod3 EC192 R	67586	-	192V*/9Ah Autonomy module		1 year	604 x 418 x 129 [3U]	49	1	
	BM Mod3 FC240 R	67587	-	240V*/9Ah Autonomy module		1 year	604 x 418 x 129 [3U]	59	1	
BM Mod3 GA384 R	67588	-	384V*/5Ah Autonomy module		1 year	604 x 418 x 129 [3U]	41	1		
Make sur to provide suitable cabinet for the depth (D) of the autonomy module. * The 192V and 240V autonomy modules are to be used in pairs										
Mod3 : Associated accessories										
A	SNMP I Pro Agent (Network Management)	61156		SNMP Agent card for UPS equipped with a SNMP slot		2 years	-	-	1	
	External SNMP I Pro Agent RS 232 (Network Management)	61830		SNMP Agent for all products equipped with a RS 232 port		2 years	-	-	1	
	SNMP Agent vm MiniSlot (Virtual Environment Network Management)	61142		vmWare®-ready SNMP Agent for virtual network CS141 Minislot (compatible with vmWare® etc.) + 1 RCCMD license		2 years	-	-	1	
	RCCMD license for virtual server management	61143		1 RCCMD Licence (1 per additional network environment) compatible with SNMP agent vm MiniSlot (ref. 61142)		2 years	-	-	1	
	Temperature & Humidity Probe - EMD	61452		Temperature and humidity detector to be connected to the SNMP I Pro agent		2 years	-	-	1	
	Temperature Probe CS141 MINI	61822		Temperature detector to be connected to the SNMP agent vm MiniSlot		2 years	-	-	1	
	Temperature & Humidity Probe CS141 MINI	61839		Temperature and humidity detector to be connected to the SNMP agent vm MiniSlot		2 years	-	-	1	
	Mod3 19U-Cabinet TT	67827		19U preconfigured Mod3 rack cabinet (3/3 version) - Connection kit included		2 years	857 x 443 x 840	72	1	
	Mod3 19U-Cabinet TM	67828		19U preconfigured Mod3 rack cabinet (3/1 version) - Connection kit included		2 years	857 x 443 x 840	72	1	
	Mod3 Control module	67835		Module with integrated dry contacts, EPO, RS232, USB and two additional slots for the SNMP cards, Modbus, AS400 ((standard for pre-configured Mod3 rack solutions)		2 years	-	-	1	
	Connection kit (UPS module)	67830		Kit for connecting the UPS in single use		2 years	275 x 434,5 x 42	3,7	1	
	Connection kit (autonomy module)	67831		Kit for connecting the autonomy module in single use		2 years	275 x 434,5 x 42	3,7	1	
	10" Touch screen	67834		10" color touch screen for Mod3		2 years	-	-	1	
	Module front panel	67832		Faceplate for masking an empty bay when a module is missing		2 years	-	-	1	

Mod3



Mod3 C 10kVA



Mod3 C 40/10 (19U)

M5T



SINGLE-PHASE INPUT / SINGLE-PHASE OUTPUT UPS

THREE-PHASE INPUT / SINGLE-PHASE OUTPUT UPS

THREE-PHASE INPUT / THREE-PHASE OUTPUT UPS

UNINTERRUPTIBLE POWER SUPPLY

— APPLICATIONS : SENSITIVE APPLICATIONS, INDUSTRIAL AND HEALTHCARE SECTORS

THREE-PHASE INPUT / THREE-PHASE OUTPUT UPS

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer		
ModST E / ModST : Modular, paralleling capability and redundant UPS (three/three) - On Line Double Conversion High Frequency Technology											
MODSTE	ModST E 60/20 S (15U) (max nb of installable power modules: 3*20 kVA)	67710	20 to 60 kVA (20 kVA power module)	Modular configuration N + X Hot swappable power modules Input/output terminal blocks 5,7" LCD screen Manual Bypass Maintenance Separate UPS power supply and manual bypass Batteries in separate cabinets	Additional Com Port : 2 contacts for SNMP 20 dry contacts Optional : 10" touch screen SNMP card	1 year	1100 x 515 x 761 (15U)	176	1		
	ModST E 90/30 S (15U) (max nb of installable power modules: 3*30 kVA)	67711	30 to 90 kVA (30 kVA power module)			1 year		180,5	1		
	ModST E 60/20 (29U) (max nb of installable power modules: 3*20 kVA)	67708	20 to 60 kVA (20 kVA power module)	Modular configuration N + X Hot swappable power modules Input/output terminal blocks 5,7" LCD screen Manual Bypass Maintenance Separate UPS power supply and manual bypass Integrated batteries		1 year	1100 x 515 x 1522 (29U)	301	1		
	ModST E 90/30 (29U) (max nb of installable power modules: 3*30 kVA)	67709	30 to 90 kVA (30 kVA power module)			1 year		305,5	1		
	ModST 80/20 S (30U) (max nb of installable power modules: 4*20 kVA)	67703	20 to 80 kVA (20 kVA power module)	Modular configuration N + X Separate network 1/network 2 power supply Hot swappable power modules Input/output terminal blocks Input: Three-phase / Output: Three-phase 5,7" LCD screen Manual Bypass Maintenance Additional autonomy modules		1 year	1100 x 600 x 1475 (30U)	363	1		
	ModST 120/20 S (30U) (max nb of installable power modules: 6*20 kVA)	67704	20 to 120 kVA (20 kVA power module)			1 year	1100 x 600 x 1475 (30U)	390	1		
	ModST 120/30 S (30U) (max nb of installable power modules: 4*30 kVA)	67705	30 to 120 kVA (30 kVA power module)			1 year	1100 x 600 x 1475 (30U)	335	1		
	ModST 180/30 S (30U) (max nb of installable power modules: 6*30 kVA)	67706	30 to 180 kVA (30 kVA power module)			1 year	1100 x 600 x 1475 (30U)	437,5	1		
	ModST 210/30 S (42U) (max nb of installable power modules: (7+1)*30 kVA)	67707	30 to 210 kVA Per power modules of 30 kVA			1 year	1100 x 600 x 2010 (42U)	549	1		
	ModST 300/30 S (42U) (max nb of installable power modules: 10*30 kVA)	67724	30 to 300 kVA (30 kVA power module)			1 year	1100 x 600 x 2010	620	1		
	ModST 90/30 (30U) (max nb of installable power modules: 3*30 kVA)	67701	30 to 90 kVA (30 kVA power module)			Modular configuration N + X Separate network 1/network 2 power supply Hot swappable power modules Input/output terminal blocks Input: Three-phase / Output: Three-phase 5,7" LCD screen Manual Bypass Maintenance Integrated batteries	1 year	1100 x 600 x 1475 (30U)	405	1	
	ModST 120/30 (42U) (max nb of installable power modules: 4*30 kVA)	67702	30 to 120 kVA (30 kVA power module)				1 year	1100 x 600 x 2010 (42U)	482	1	
	ModST 120/60 (30U) (max nb of installable power modules: 2*60 kVA)	67736	60 to 120 kVA (60 kVA power module)			Modular configuration N + X Separate network 1/network 2 power supply Hot swappable power modules Input/output terminal blocks Input: Three-phase / Output: Three-phase 10" LCD screen Manual Bypass Maintenance Additional autonomy modules	1 year	600 x 1100 x 1475 (30U)	308	1	
	ModST 180/60 (30U) (max nb of installable power modules: 3*60 kVA)	67737	60 to 180 kVA (60 kVA power module)				1 year	600 x 1100 x 1475 (30U)	352	1	
	ModST 240/60 (42U) (max nb of installable power modules: 4*60 kVA)	67738	60 to 240 kVA (60 kVA power module)	1 year			600 x 1100 x 2010 (42U)	466	1		
	ModST 300/60 (42U) (max nb of installable power modules: 5*60 kVA)	67739	60 to 300 kVA (60 kVA power module)	1 year			600 x 1100 x 2010 (42U)	510	1		
	ModST 420/60 (42U) (max nb of installable power modules: 7*60 kVA)	67740	60 to 420 kVA (60 kVA power module)	1 year			1200 x 1100 x 2010 (42U)	888	1		
	ModST 500/60 (42U) (max nb of installable power modules: 8*60 kVA)	67741	60 to 480 kVA (60 kVA power module)	1 year			1200 x 1100 x 2010 (42U)	932	1		
	ModST 600/60 (42U) (max nb of installable power modules: 10*60 kVA)	67742	60 to 600 kVA (60 kVA power module)	1 year			1200 x 1100 x 2010 (42U)	1020	1		
	For any particular configuration and extended autonomy battery cabinets, please contact us										
ModST / ModST E : Power & backup modules - Autonomy extensions											
B	20kVA power module	67801	20 kVA	20kVA / 20 kW Power module	1 year		132 x 440 x 650 (3U)	34	1		
	30kVA power module	67802	30 kVA	30kVA / 30 kW Power module	1 year	132 x 440 x 650 (3U)	34,5	1			
	60kVA power module	67836	60 kVA	60kVA / 60 kW Power module	1 year	750 x 438 x 130 (3U)	44	1			
	Batteries module (ModST)	67585	-	4 drawers make up an empty battery module	1 year	155 x 107 x 735	26	1			
	BM ModST LC480 T	67712	-	Compatible with ModST 30U	2 years	1100 x 600 x 1475	905	1			
	BM ModST MC480 T	67713	-	Compatible with ModST 42U	2 years	1100 x 600 x 2010	1300	1			
	BM ModST HK480 T	67714	-	Compatible with ModST 42U	2 years	1100 x 600 x 2010	1407	1			
	BM ModST E KC480 T	67715	-	Compatible with ModST E 15U	2 years	1000 x 515 x 761	407	1			
ModST / ModST E : Associated accessories											
A	SNMP I Pro Agent (Network Management)	61156	SNMP Agent card for UPS equipped with a SNMP slot			2 years	-	-	1		
	SNMP Agent vm MiniSlot (Virtual Environment Network Management)	61142	vmWare®-ready SNMP Agent for virtual network CS141 MiniSlot (compatible with vmWare® etc.) + 1 RCCMD license			2 years	-	-	1		
	Temperature & Humidity Probe - EMD	61452	Temperature and humidity detector to be connected to the SNMP I Pro agent			2 years	-	-	1		
	Temperature Probe CS141 MINI	61822	Temperature detector to be connected to the SNMP agent vm MiniSlot			2 years	-	-	1		
	Temperature & Humidity Probe CS141 MINI	61839	Temperature and humidity detector to be connected to the SNMP agent vm MiniSlot			2 years	-	-	1		
	10" Touch screen	67817	Door and 10" color touch screen for ModST			2 years	-	-	1		
	Communication card	67816	Additional programmable communication card for ModST			2 years	-	-	1		



For any particular configuration, please contact us

Tel : +33 (0)2 40 76 11 77
Fax : +33 (0)2 40 96 29 51
commercial@infosec.fr

Sales department



Subscribe to an Infosec **maintenance contract** !

Discover all Infosec services in our dedicated documentation !

UNINTERRUPTIBLE POWER SUPPLY

—⊙ APPLICATIONS : EXTENDED AUTONOMIES OTHER THAN COMPUTING

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer
G1 / G1 Solar MPPT : UPS for extended autonomies - High Frequency Technology									
	G1 5KW	63228	5000 VA	DC/AC inverter 60A battery charger Up to 9 units in parallel (5 kW per unit) 19" rack format LCD display MPPT technology (G1 Solar MPPT)	RS 232 / RS 485 Ports SNMP Option	2 years	400 x 438 x 88 (2U)	9.1	8
	G1 SOLAR MPPT 5Kw	63229	5000 VA						8
G1 / G1 Solar MPPT : Associated Accessory									
	G1 SNMP Agent (Network Management)	61199		Embeddable SNMP agent card for G1 and G1 Solar MPPT		2 years	-	-	1



SERVICES

—⊙ ADDITIONAL AND OPTIONAL SERVICES

INSURANCE

Infosec Communication offers free of charge insurance for connected equipment on most UPS, surge protectors and energy savers.

PRODUCT
100 %
WARRANTED

WARRANTY EXTENSIONS

In order to ensure maximum protection of your system, Infosec Communication offers 3 year warranty extensions for UPS below 5kVA (for higher powers, see «Maintenance Contracts»).



MAINTENANCE CONTRACTS

In order to ensure a perfect protection and optimized lifespan of your equipment, Infosec offers 3 types of maintenance contracts for the 5kVA and above On Line range of UPS:

- Excellence Contract
- Advantage Contract
- Premium Contract



Ask us for our service documentation

OTHER ACCESSORIES & EQUIPMENTS

Series	Model	SKU	Features	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer
⊕ ADDITIONAL ACCESSORIES FOR UPS							
A	RJ11/RJ11 cable	61431	RJ11 cable	-	-	-	1
	IEC MF C13/C14_10A cable	61401	IEC M/F 10A cord	-	-	-	1
	IEC 16A MF C19/C20 cable	61456	IEC M/F 16A cord	-	-	-	1
	10A FR-SCHUKO/IEC C13 power cable	61432	10A power cord for IEC power supply	-	-	-	1
	IEC-C14 / 3 FR outlets adaptor	61402	IEC cord + 3 FR (2P+T) outlets	-	-	-	1
	ATS Automatic Transfer Switch 1/3k	61453	16A Power transfer system	2 years	330 x 483 x 44	5	1
	Isolation transformer	-	Available in different powers and for different products - consult us	-	-	-	1
	Smart Charger S - 24 VDC	61139	External charger for 24V battery module - 2 to 6A	2 years	83 x 150 x 220	2	1
	Smart Charger S - 48 VDC	61140	External charger for 48V battery module - 2 to 6A	2 years		2	1
	Smart Charger S - 72 VDC	61141	External charger for 72V battery module - 2 to 6A 2 years	2 years		2,5	1
⊕ COMMUNICATION SOLUTIONS FOR NETWORKED UPS AND VIRTUAL ENVIRONMENTS (VMWARE®, Hyper VTM, etc.)							
A	SNMP I Pro Agent (Network Management)	61156	SNMP Agent card for UPS equipped with a SNMP slot	2 years	-	-	1
	External SNMP agent USB (Network management)	61823	DY 630 USB SNMP Agent for all products equipped with a USB port	2 years	-	-	1
	External SNMP I Pro Agent RS 232 (Network Management)	61830	SNMP Agent for all products equipped with a RS 232 port	2 years	-	-	1
	SNMP Agent vm MiniSlot (Virtual Environment Network Management)	61142	vmWare®-ready SNMP Agent for virtual network CS141 Minislot (compatible with vmWare® etc.) + 1 RCCMD license	2 years	-	-	1
	RCCMD license for virtual server management	61143	1 RCCMD Licence (1 per additional network environment) compatible with SNMP agent vm MiniSlot (ref. 61142)	2 years	-	-	1
	Temperature Probe CS141 MINI	61822	Temperature detector to be connected to the SNMP agent vm MiniSlot	2 years	-	-	1
	Temperature & Humidity Probe CS141 MINI	61839	Temperature and humidity detector to be connected to the SNMP agent vm MiniSlot	2 years	-	-	1
	Temperature & Humidity Probe - EMD	61452	Temperature and humidity detector to be connected to the SNMP I Pro agent	2 years	-	-	1

BATTERIES

Series	Model	SKU	Type	Description	War.	Dimensions dxwxh (mm)	Weight (kg)
Batteries - UPS spare parts							
A	BATTERY 12V - 5 Ah	61989	12V 5Ah	BAT. LEOCH LHR1224W	1 year	107 x 70 x 90	1,9
	BATTERY 12V - 7,2 Ah	61902	12V 7,2Ah	BAT. CSB GP1272F2	1 year	151 x 65 x 100	2,3
	BATTERY 12V - 9 Ah	61988	12V 9Ah	BAT. CSB HR1234WF2	1 year		2,5

RACKMOUNTABLE POWER DISTRIBUTION

Series	Model	SKU	Features	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer
PDU - A complete range of rackmountable distribution strips							
PDU	L4 RM	61470	1U PDU 4 FR outlets	1 year	255 x 44,4 x 44,4	0,6	1
	L6 RM	61471	1U PDU 19" 6 FR outlets	1 year	485 x 45 x 45	0,8	1
	L6 RM plus	61472	1U PDU 19" 6 FR outlets + 16A circuit breaker	1 year	485 x 46,5 x 44,4	1,2	1
	L8 RM	61473	1U PDU 19" 8 FR outlets	1 year	485 x 45 x 45	0,9	1
	L9 RM	61474	1U PDU 19" 9 FR outlets	1 year	485 x 45 x 45	0,9	1
	L8 RM C14	61475	PDU 19" 8 FR outlets + IEC C14 power cable (10A) For UPS with IEC 10A C13 output	1 year	485 x 45 x 45	0,9	1
	L9 RM C20	61476	19" PDU 9 FR outlets + IEC C20 power cable (16A) For UPS with IEC 16A C19 output	1 year	485 x 45 x 45	0,9	1
	L10 RM C14	61477	19" PDU 10 IEC outlets + IEC C14 power cable (10A) For UPS with IEC 10A C13 output	1 year	485 x 46 x 44,4	0,9	1
	L10 RM C20	61478	19" PDU 10 IEC outlets + IEC C20 power cable (16A) For UPS with IEC 16A C19 output	1 year	485 x 46 x 44,4	0,9	1
	L18 VM plus	61479	Vertical PDU 18 FR outlets + 2 circuit breakers (1 for 9 outlets) + 2m cable For connection on terminal block from 5kVA	1 year	44,4 x 44,4 x 1100	2,2	1
	L20 VM plus	61480	Vertical PDU 20 IEC outlets + 2 circuit breakers (1 for 10 outlets) + 2m cable For connection on terminal block from 5kVA	1 year	44,4 x 44,4 x 1100	2	1

PDU



L8 RM C14



SNMP I Pro



SNMP vm Minislot



Smart Charger S



L9 RM C20



DY 630 USB SNMP Agent



Power cord



REGULATORS

— APPLICATIONS : AVR

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer
R1 USB : Voltage regulator - Compatible with wide input voltage ranges									
R1 USB	R1 USB 600	63168	600 VA	Relay technology 3 FR/SCHUKO outlets USB charger 3 status indicators	-	2 years	180 x 95 x 119	1,3	8
	R1 USB 1000	63169	1000 VA					1,6	8
	R1 USB 1500	63170	1500 VA					1,9	8
R2 Pro : Voltage Regulator - Compatible with wide input voltage ranges									
R2 PRO	R2 PRO 1500	63148	1500 VA	Relay technology 2 FR/SCHUKO outlets LCD display	Control panel	1 year	150 x 140 x 200	5	4
	R2 PRO 2000	63149	2000 VA				220 x 160 x 180	5,9	4
	R2 PRO 3000	63150	3000 VA				280 x 200 x 220	7,8	2
	R2 PRO 5000	63151	5000 VA	Relay technology Terminal block LCD display			340 x 210 x 280	9,6	2
	R2 PRO 10k	63153	10000 VA				410 x 280 x 300	16,5	1
	R2 PRO 20k	63155	20000 VA				360 x 450 x 592	42	1

R1
USB



R2
PRO



INVERTER CHARGERS

— APPLICATIONS : RENEWABLE ENERGIES / SELF-PRODUCED ENERGY

Series	Model	SKU	Power	Features	Communication	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer
C2 : 2 in 1 Inverter charger									
C2	C2 Nomad combo 4000-48V	63208	4000 VA	Photovoltaic DC/AC inverter Delivers a sinusoidal current and a 230V voltage from the batteries Accepts multiple power sources: Photovoltaic panel, grid/generator IP23 protection rating LCD display	RJ45 (RS 232) Ports Software : WatchPower	2 years	120 x 295 x 468	10	1
C3 : 2 in 1 Inverter charger with MPPT technology									
C3	C3 MPPT 1000-48V	63211	1000 VA	MPPT Technology Photovoltaic DC/AC inverter Delivers a sinusoidal current and a 230V voltage from the batteries Accepts multiple power sources: Photovoltaic panel, grid/generator IP23 protection rating LCD display	RJ45 (RS 232) Ports Software : WatchPower	2 years	120 x 280 x 375	6,8	1
	C3 + MPPT 2000-48V	63213	2000 VA				140 x 295 x 479	11,50	1
	C3 + MPPT 4000-48V	63216	4000 VA				540 x 295 x 140	12,50	1
C2 Nomad Combo and C3 MPP : Associated accessories									
A	Paralleling kit	61712	-	Paralleling kit C3+ MPPT 4000-5000VA	-	2 years	-	-	1
	Remote control display	61713	-	C3 MPPT External control unit		2 years	198 x 162 x 88	-	1

C2



C3



OTHER ACCESSORIES & EQUIPMENT

—⊙ NOMAD ENERGY

Series	Model	SKU	Features	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer
	Travel adapter	61514	Travel adapter (European, American, Australian plug...) with built-in USB charger	2 years	82 x 50 x 28	0,08	10

SURGE PROTECTORS

—⊙ APPLICATIONS : DIGITAL ENTERTAINMENT

Series	Model	SKU	Features	Equip war	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer
	S4 Black Line II	61294	4 FR outlets with surge protection	2 500 €	2 years	300 x 55 x 40	0,38	20
	S5 Black Line II	61295	5 FR outlets with surge protection	2 500 €	2 years	350 x 55 x 40	0,44	20
	S6 Black Line II	61296	6 FR outlets with surge protection	2 500 €	2 years	400 x 55 x 40	0,52	20

—⊙ APPLICATIONS : DIGITAL ENTERTAINMENT & MULTIMEDIA

Series	Model	SKU	Features	Equip war	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer
	S1 USB NEO	61297	1 FR outlet with surge protection - 2 USB chargers (2.1A)	15 000 €	2 years	106 x 76 x 80	0,16	20
	S5 USB NEO	61298	5 FR outlets with surge protection - 2 USB chargers (2.1A)	50 000 €	2 years	371 x 64 x 39,5	0,52	20

—⊙ APPLICATIONS : SIMPLE ELECTRICAL EQUIPMENT

Series	Model	SKU	Features	Equip war	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer
	S5	61270	5 FR outlets with surge protection	50 000 €	2 years	370 x 62 x 50	0,48	20
	S8	61272	8 FR outlets with surge protection	50 000 €	2 years	360 x 135 x 63	0,79	10

—⊙ APPLICATION : PERSONAL COMPUTING & MULTIMEDIA

Series	Model	SKU	Features	Equip war	War.	Dimensions dxwxh (mm)	Weight (kg)	Per Outer
	S1 LAN	61269	1 FR outlet with surge protection - RJ45 (In/Out)	15 000 €	2 years	95 x 65 x 85	0,10	20
	S5 LAN	61271	5 FR outlets with surge protection - RJ45 (In/Out)	50 000 €	2 years	370 x 62 x 50	0,48	20
	S8 LAN TV	61273	8 FR outlets with surge protection - RJ45 (In/Out) TV antenna protection (coaxial cable connectors)	50 000 €	2 years	360 x 135 x 63	0,79	10



L'Énergie Sans Limite !
Safe Energy for Life !

Tel : +33 (0)2 40 76 11 77
Fax : +33 (0)2 40 96 29 51
sales@infosec.fr

Sales department

Tel : +33 (0)2 40 76 15 82
hotline@infosec.fr

Hotline